

## AGRIMAX RT 855 - Specifiche tecniche



### Description

AGRIMAX RT 855 si distingue per l'eccellente trazione e il comfort. Principalmente sviluppato per la lavorazione del terreno e il trasporto sia su campo che sulla strada, alcune misure sono anche idonee per applicazioni di irrorazione e vendemmia. AGRIMAX RT 855 possiede ottime doti di autopulitura che consentono il rapido cambio dalle operazioni sul campo all'impiego su strada.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricoltura: Macchina irroratrice • Trattore • Vendemmiatrice

Version	STANDARD
Type	TL
Tyre Size	380/85 R 34 (14.9 R 34)
LI/SS	137 A8/B

## Dimensions US Standard

Usa code	94021697
Section Width (inch)	15
Overall Diameter (inch)	59.4
Static Loaded Radius (inch)	26.9
Rolling Circumference (inch)	177.3
Rim Rec	W 12
Rim Alt	W 11 ; W 13
ECE	E4-106R-000655
TRA Code	R1W

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23
30	2790	3250	3700	4170	4620	5080
25	2790	3250	3700	4170	4620	5080
20	3000	3480	3970	4460	4950	5430
5 LT	3750	4350	4970	5580	6190	6800
5 HT	3000	3480	3970	4460	4950	5430

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 05:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..