

AGRIMAX RT 855 - Specifiche tecniche



Description

AGRIMAX RT 855 si distingue per l'eccellente trazione e il comfort. Principalmente sviluppato per la lavorazione del terreno e il trasporto sia su campo che sulla strada, alcune misure sono anche idonee per applicazioni di irrorazione e vendemmia. AGRIMAX RT 855 possiede ottime doti di autopulitura che consentono il rapido cambio dalle operazioni sul campo all'impiego su strada.

UM

US Standard

Construction

 RADIAL

Machinery

Agricoltura: Macchina irroratrice • Trattore • Vendemmiatrice

Version	STANDARD
Type	TL
Tyre Size	520/85 R 42 (20.8 R 42)
LI/SS	167 A8/B

Dimensions US Standard

Usa code	94040513
Section Width (inch)	20.3
Overall Diameter (inch)	76.8
Static Loaded Radius (inch)	33.8
Rolling Circumference (inch)	227.6
Rim Rec	DW 16 L ; W 16 A ; DD 16
Rim Alt	DW 18 A ; DD 18 ; W 18 A ; DD 18 L
ECE	E4-106R-001491
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	35	41	46
30	5000	5820	6650	7460	8280	9090	10220	11180	12010
25	5000	5820	6650	7460	8280	9090	10220	11180	12010
20	5360	6240	7110	7990	8860	9730	10930	11960	12850
5 LT	6710	7800	8910	10000	11100	12190	13690	14980	16100
5 HT	5360	6240	7110	7990	8860	9730	10930	11960	12850

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 07:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..