

AGRIMAX RT 955 - Specifiche tecniche



Description

AGRIMAX RT 955 è uno pneumatico radiale BKT ideale per le applicazioni di colture a filari, mentre alcune misure sono anche idonee per irrorazione e vendemmia. Lo speciale disegno del battistrada con spalla arrotondata si traduce in eccellente trazione nonché ottime stabilità e proprietà di autopulitura. Grazie alla carcassa robusta, AGRIMAX RT 955 assicura un'elevata capacità di carico.

UM

US Standard

Construction

 RADIAL

Machinery

Agricoltura: Macchina irroratrice • Vendemmiatrice

Version	STANDARD
Type	TL
Tyre Size	230/95 R 44 (9.5 R 44)
LI/SS	134 A8/B

Dimensions US Standard

Usa code	94027415
Section Width (inch)	9
Overall Diameter (inch)	61.3
Static Loaded Radius (inch)	29.1
Rolling Circumference (inch)	188.5
Rim Rec	W 7
Rim Alt	W 8
ECE	E4-106R-000777
TRA Code	R1

Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46	52	58	64
30	1830	2390	2900	3190	3370	3690	4020	4350	4670	-
25	1830	2390	2900	3190	3370	3690	4020	4350	4670	-
20	1960	2560	3110	3410	3600	3960	4310	4660	5000	-
5	2180	2740	3370	4000	4630	4770	5330	5900	6460	7010

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 22:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..