

## AGRIMAX RT 955 - Specifiche tecniche



### Description

AGRIMAX RT 955 è uno pneumatico radiale BKT ideale per le applicazioni di colture a filari, mentre alcune misure sono anche idonee per irrorazione e vendemmia. Lo speciale disegno del battistrada con spalla arrotondata si traduce in eccellente trazione nonché ottime stabilità e proprietà di autopulitura. Grazie alla carcassa robusta, AGRIMAX RT 955 assicura un'elevata capacità di carico.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricoltura: Macchina irroratrice • Vendemmiatrice

|           |                            |
|-----------|----------------------------|
| Version   | STANDARD                   |
| Type      | TL                         |
| Tyre Size | 300/95 R 46<br>(12.4 R 46) |
| LI/SS     | 148 A8/B                   |

## Dimensions International Standard

|                            |                             |
|----------------------------|-----------------------------|
| Section Width (mm)         | 295                         |
| Overall Diameter (mm)      | 1738                        |
| Static Loaded Radius (mm)  | 812                         |
| Rolling Circumference (mm) | 5318                        |
| SRI (mm)                   | 825                         |
| Rim Rec                    | W 9                         |
| Rim Alt                    | W 10 ; W 11 ; DW 10 ; DW 11 |
| ECE                        | E4-106R-000790              |
| TRA Code                   | R1                          |

## Load capacity (Kg)

| km/h / bar | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  | 3.6  | 4.0  | 4.4  |
|------------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| 50         | 1105 | 1295 | 1485 | 1670 | 1860 | 2020 | 2205 | 2365 | 2585 | 2805 | 2995 | 3150 | -    |
| 40         | 1105 | 1295 | 1485 | 1670 | 1860 | 2020 | 2205 | 2365 | 2585 | 2805 | 2995 | 3150 | -    |
| 30         | 1185 | 1385 | 1590 | 1790 | 1995 | 2160 | 2365 | 2535 | 2770 | 3005 | 3210 | 3375 | -    |
| 20         | 1360 | 1590 | 1825 | 2055 | 2290 | 2480 | 2715 | 2910 | 3180 | 3450 | 3685 | 3875 | -    |
| 10         | 1525 | 1785 | 2045 | 2310 | 2570 | 2785 | 3045 | 3265 | 3570 | 3875 | 4135 | 4350 | 4725 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 22:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..