

AGRIMAX TERIS - Scheda tecnica



Description

Le mietitrici ad elevata potenza di oggi richiedono pneumatici che siano in grado di sopportare macchine e carichi pesanti senza danneggiare le colture. BKT si impegna ad offrirvi soluzioni di pneumatici radiali all'avanguardia per aumentare il rendimento del vostro raccolto. AGRIMAX TERIS è il partner ideale per le vostre operazioni combinate. Eccellenti proprietà di trazione e elevata capacità di carico sono le sue caratteristiche essenziali che si traducono in performance straordinarie in tutte le operazioni di raccolta. La speciale protezione del fianco e la spalla rinforzata aumentano la resistenza - prolungando quindi il ciclo di vita del prodotto - anche in condizioni difficili e nella presenza di stoppie sul campo.

UM

US Standard

Construction

 RADIAL

Machinery

Agricoltura: Raccogliatrice di cotone • Mietitrebbia

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
620/75 R 26 CHO	STANDARD	94035809	166 A8/B	DW 20 B		24.6	62.6	28.7	191	TL	E4-106R-001419
750/65 R 26 CHO (28L R 26)	STANDARD	94039111	171 A8/B	DW 25 B	DW 23 B	30.1	64.4	28.1	193.2	TL	E4-106R-001496
750/65 R 26 CHO (28L R 26)	STANDARD	94030668	166 A8/B	DW 25 B	DW 23 B	30.1	64.4	28.1	193.2	TL	E4-106R-000810
710/55 R 28 CHO	STANDARD	94060023	164 A8/B	DW 23 B		28.2	58.8	26.1	174.9	TL	E11-106R-005940
620/75 R 30 CHO	STANDARD	94039586	168 A8/B	DW 20 B		24.6	66.6	30.7	203.5	TL	E4-106R-001420
1050/50 R 32 CHO	HD	94076185	184 A8/181 B	36.0 VA		41.7	74.5	33.1	223.8	TL	E11-106R-0010258
1050/50 R 32 CHO	STANDARD	94032723	184 A8/181 B	36.0 VA		41.7	74.5	33.1	223.8	TL	E4-106R-000813
650/75 R 32 CHO	STANDARD	94032860	172 A8/B	DW 21 B	DW 20 B ; DW 23 B	26.4	70.7	32.1	211.7	TL	E4-106R-001425
800/65 R 32 CHO (30.5L R 32)	STANDARD	94031412	178 A8/175 B	DW 27 B	DW 25 B ; DH 27 B	32.2	73	33	218.5	TL	E4-106R-001430
900/60 R 32 CHO	STANDARD	94040865	185 A8/182 B	DW 27 B	DW 28 B ; DW 30 B	34.4	75.2	34.4	227.4	TL	E4-106R-001433
900/60 R 32 CHO	STANDARD	94029723	181 A8/178 B	DW 27 B	DW 28 B ; DW 30 B	34.9	75.2	33.6	224.4	TL	E4-106R-001431
IF 710/75 R 32 CFO	STANDARD	94059249	183 A8/B	DW 25 B	DW 23 B	28.2	74	33.5	222.6	TL	E11-106R-005025
IF 580/80 R 34 CFO	STANDARD	94044641	177 D	DW 20 B ; DW 20 A	DW 21 A ; DW 21 B	23.1	70.6	31.9	213.5	TL	E4-106R-001833
IF 710/75 R 34 CFO	STANDARD	94058723	184 A8/B	DW 25 B		28.2	76	34.3	230.4	TL	E11-106R-004899
520/85 R 42	STANDARD	94044634	168 D	DW 16 L	W15L ; DW15L ; DD16L ; W16L ; DD18L ; DW18L ; W18L	20.3	76.8	35	230.4	TL	E4-106R-001829

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 05:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..