

AIROMAX AM 28 WINTER - Specifiche tecniche



Description

AIROMAX AM28 WINTER è stato progettato specificatamente per le gru mobili ad alta velocità del settore edile. Infatti, questo pneumatico BKT è ottimizzato per affrontare i task più impegnativi nei cantieri che richiedono una manovrabilità precisa ad alte velocità fino a 80 km/h (50 mph). AIROMAX AM28 WINTER è stato realizzato con una mescola particolarmente resistente al calore, una caratteristica importante per ambienti così impegnativi. Il disegno a blocchi del battistrada, appositamente sviluppato con numerose scanalature sottili e dentellate, assicura aderenza e trazione eccellenti, evitando lo slittamento anche su ghiaccio e neve. Infine, lo pneumatico offre un comfort di guida eccezionale e fluido, anche durante le operazioni di servizio gravose.

UM

International Standard

Construction

 RADIAL

Machinery

Industriale: Gru mobile

Version	STANDARD
Type	TL
Tyre Size	445/95 R 25 (16.00 R 25)
LI/SS	174 F

Dimensions International Standard

Overall Width (mm)	435
Overall Diameter (mm)	1487
Static Loaded Radius (mm)	694
Rolling Circumference (mm)	4578
Rim Rec	11.25/2.0
Rim Alt	11.00/1.7 CR ; 11.00/1.7CRL
ECE	E4-54R-0022146

Load capacity (Kg)

km/h / bar	9.00
30	8500
40	7750
50	7500
60	7300
70	7100
80	6700
90	6300
100	5600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/11/2024 23:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..