

## AIROMAX AM 28 WINTER - Specifiche tecniche



### Description

AIROMAX AM28 WINTER è stato progettato specificatamente per le gru mobili ad alta velocità del settore edile. Infatti, questo pneumatico BKT è ottimizzato per affrontare i task più impegnativi nei cantieri che richiedono una manovrabilità precisa ad alte velocità fino a 80 km/h (50 mph). AIROMAX AM28 WINTER è stato realizzato con una miscela particolarmente resistente al calore, una caratteristica importante per ambienti così impegnativi. Il disegno a blocchi del battistrada, appositamente sviluppato con numerose scanalature sottili e dentellate, assicura aderenza e trazione eccellenti, evitando lo slittamento anche su ghiaccio e neve. Infine, lo pneumatico offre un comfort di guida eccezionale e fluido, anche durante le operazioni di servizio gravose.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Industriale: Gru mobile

Version	STANDARD
Type	TL
Tyre Size	445/95 R 25 (16.00 R 25)
LI/SS	174 F

## Dimensions US Standard

Usa code	94069927
Overall Width (inch)	17.1
Overall Diameter (inch)	58.5
Static Loaded Radius (inch)	27.3
Rolling Circumference (inch)	180.2
Rim Rec	11.25/2.0
Rim Alt	11.00/1.7 CR ; 11.00/1.7CRL
ECE	E4-54R-0022146

## Load capacity (lbs)

mph / psi	130
20	18700
25	17100
30	16500
35	16100
43	15700
50	14800
55	13900
62	12300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/11/2024 23:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..