

## AS 504 - Specifiche tecniche



### Description

AS 504 è uno pneumatico agro-industriale principalmente sviluppato per le operazioni di lavorazioni della terra, attrezzi agricoli e movimentazione di materiali. Questo pneumatico che si distingue per le eccellenti proprietà di autopulitura e il grip potenziato, è ideale per rimorchi e sollevatori telescopici. AS 504 è disponibile in diverse versioni al fine di soddisfare le esigenze specifiche dell'utilizzatore: una versione "HD" con miscela speciale resistente a tagli e lacerazioni, mentre la versione "special" è dotata di una carcassa rinforzata che assicura una vita prolungata dello pneumatico.

### UM

International Standard

### Construction

BIAS

### Machinery

Agricoltura: Sollevatore telescopico • Rimorchio da campo  
Industriale: Sollevatore telescopico

Version	STUBBLE RESISTANT
Type	TL
Tyre Size	11.5/80 - 15.3
LI/SS DRIVE WHEEL	123 A8
LI/SS FREE ROLLING	135 A8

## Dimensions International Standard

Ply Rating	12
Section Width (mm)	290
Overall Diameter (mm)	867
Static Loaded Radius (mm)	380
Rolling Circumference (mm)	2540
SRI (mm)	410
Rim Rec	9.00
ECE	E11-106R-007157

## Load capacity (Kg)

km/h / bar	4.10
10 FR	3050
25 FR	2595
30 FR	2440
40 FR	2180
10 DW	2170
25 DW	1845
30 DW	1735
40 DW	1550

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 09:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..