

AS 504 - Specifiche tecniche



Description

AS 504 è un pneumatico agro-industriale principalmente sviluppato per le operazioni di lavorazioni della terra, attrezzi agricoli e movimentazione di materiali. Questo pneumatico che si distingue per le eccellenti proprietà di autopulitura e il grip potenziato, è ideale per rimorchi e sollevatori telescopici. AS 504 è disponibile in diverse versioni al fine di soddisfare le esigenze specifiche dell'utilizzatore: una versione "HD" con miscela speciale resistente a tagli e lacerazioni, mentre la versione "special" è dotata di una carcassa rinforzata che assicura una vita prolungata dello pneumatico.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Sollevatore telescopico • Rimorchio da campo
Industriale: Sollevatore telescopico

| | |
|--------------------|----------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 11.5/80 - 15.3 |
| LI/SS DRIVE WHEEL | 114 A8 |
| LI/SS FREE ROLLING | 126 A8 |

Dimensions US Standard

| | |
|------------------------------|----------------|
| Usa code | 94018673 |
| Ply Rating | 8 |
| Section Width (inch) | 11.4 |
| Overall Diameter (inch) | 34.1 |
| Static Loaded Radius (inch) | 15 |
| Rolling Circumference (inch) | 100 |
| Rim Rec | 9.00 |
| ECE | E4-106R-001892 |

Load capacity (lbs)

| mph / psi | 39 |
|-----------|------|
| 5 FR | 5250 |
| 15 FR | 4460 |
| 20 FR | 4200 |
| 25 FR | 3750 |
| 5 DW | 3640 |
| 15 DW | 3100 |
| 20 DW | 2910 |
| 25 DW | 2600 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 09:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..