

## AS 504 - Specifiche tecniche



### Description

AS 504 è uno pneumatico agro-industriale principalmente sviluppato per le operazioni di lavorazioni della terra, attrezzi agricoli e movimentazione di materiali. Questo pneumatico che si distingue per le eccellenti proprietà di autopulitura e il grip potenziato, è ideale per rimorchi e sollevatori telescopici. AS 504 è disponibile in diverse versioni al fine di soddisfare le esigenze specifiche dell'utilizzatore: una versione "HD" con miscela speciale resistente a tagli e lacerazioni, mentre la versione "special" è dotata di una carcassa rinforzata che assicura una vita prolungata dello pneumatico.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricoltura: Sollevatore telescopico • Rimorchio da campo  
Industriale: Sollevatore telescopico

Version	STANDARD
Type	TT
Tyre Size	5.00 - 15
LI/SS DRIVE WHEEL	67 A8
LI/SS FREE ROLLING	79 A8

## Dimensions International Standard

Ply Rating	4
Section Width (mm)	140
Overall Diameter (mm)	657
Static Loaded Radius (mm)	308
Rolling Circumference (mm)	1957
SRI (mm)	310
Rim Rec	3.50 D
Rim Alt	3.00 D ; 4.00 E ; 4 J
ECE	E11-106R-004237

## Load capacity (Kg)

	km/h / bar	2.30
	10 FR	610
	25 FR	520
	30 FR	485
	40 FR	435
	10 DW	425
	25 DW	365
	30 DW	340
	40 DW	305

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 22:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..