

AS 504 - Specifiche tecniche



Description

AS 504 è un pneumatico agro-industriale principalmente sviluppato per le operazioni di lavorazioni della terra, attrezzi agricoli e movimentazione di materiali. Questo pneumatico che si distingue per le eccellenti proprietà di autopulitura e il grip potenziato, è ideale per rimorchi e sollevatori telescopici. AS 504 è disponibile in diverse versioni al fine di soddisfare le esigenze specifiche dell'utilizzatore: una versione "HD" con miscela speciale resistente a tagli e lacerazioni, mentre la versione "special" è dotata di una carcassa rinforzata che assicura una vita prolungata dello pneumatico.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Sollevatore telescopico • Rimorchio da campo
Industriale: Sollevatore telescopico

| | |
|--------------------|-----------|
| Version | STANDARD |
| Type | TT |
| Tyre Size | 7.5L - 15 |
| LI/SS DRIVE WHEEL | 100 A8 |
| LI/SS FREE ROLLING | 113 A8 |

Dimensions International Standard

| | |
|----------------------------|-------------------|
| Ply Rating | 8 |
| Section Width (mm) | 210 |
| Overall Diameter (mm) | 765 |
| Static Loaded Radius (mm) | 354 |
| Rolling Circumference (mm) | 2280 |
| Rim Rec | 6 LB |
| Rim Alt | 5 K ; 5½ J ; 5½ K |
| ECE | E4-106R-002632 |

Load capacity (Kg)

| | km/h / bar | 3.70 |
|--|------------|------|
| | 10 FR | 1610 |
| | 25 FR | 1370 |
| | 30 FR | 1290 |
| | 40 FR | 1150 |
| | 10 DW | 1120 |
| | 25 DW | 950 |
| | 30 DW | 895 |
| | 40 DW | 800 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 22:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..