

## AS 504 - Specifiche tecniche



### Description

AS 504 è un pneumatico agro-industriale principalmente sviluppato per le operazioni di lavorazioni della terra, attrezzi agricoli e movimentazione di materiali. Questo pneumatico che si distingue per le eccellenti proprietà di autopulitura e il grip potenziato, è ideale per rimorchi e sollevatori telescopici. AS 504 è disponibile in diverse versioni al fine di soddisfare le esigenze specifiche dell'utilizzatore: una versione "HD" con miscela speciale resistente a tagli e lacerazioni, mentre la versione "special" è dotata di una carcassa rinforzata che assicura una vita prolungata dello pneumatico.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricoltura: Sollevatore telescopico • Rimorchio da campo  
Industriale: Sollevatore telescopico

Version	STANDARD
Type	TT
Tyre Size	7.5L - 15
LI/SS DRIVE WHEEL	100 A8
LI/SS FREE ROLLING	113 A8

## Dimensions US Standard

Usa code	94019403
Ply Rating	8
Section Width (inch)	8.3
Overall Diameter (inch)	30.1
Static Loaded Radius (inch)	13.9
Rolling Circumference (inch)	89.8
Rim Rec	6 LB
Rim Alt	5 K ; 5½ J ; 5½ K
ECE	E4-106R-002632

## Load capacity (lbs)

mph / psi	54
5 FR	3550
15 FR	3020
20 FR	2840
25 FR	2540
5 DW	2470
15 DW	2090
20 DW	1970
25 DW	1760

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 22:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..