

## AS 511 - Specifiche tecniche



### Description

AS 511 è particolarmente idoneo per attrezzi agricoli nelle applicazioni con manti erbosi. La carcassa robusta e la miscela del battistrada particolarmente resistente ai tagli garantiscono straordinaria stabilità e performance avanzate. Grazie alla larga area di contatto, AS 511 offre eccellente trazione e minimizza la compattazione del suolo.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricoltura: Attrezzi agricoli

Version	STANDARD
Type	TL
Tyre Size	33 X 15.50 R 15
LI/SS	126 B

## Dimensions International Standard

Section Width (mm)	404
Overall Diameter (mm)	840
Static Loaded Radius (mm)	375
Rolling Circumference (mm)	2533
SRI (mm)	400
Rim Rec	13 LB
ECE	E11-106R-0010516

## Load capacity (Kg)

km/h / bar	2.8
50	1700

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/02/2025 10:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..