

AT 108 - Specifiche tecniche

Description

AT 108 è uno pneumatico per ogni tipo di terreno per i veicoli ATV. Il disegno del battistrada assicura comfort e performance eccellenti su strada e fuori strada.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Veicolo ATV



Version	STANDARD
Type	TL
Tyre Size	AT 25 X 12 - 10

Dimensions International Standard

Ply Rating	6
Section Width (mm)	298
Overall Diameter (mm)	630
Rim Rec	9.5 AT
Rim Alt	9.0 AT ; 10.0 AT

Load capacity (Kg)

km/h / bar	0.45
80	224

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24/11/2024 02:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..