

AT 108 - Scheda tecnica

Description

AT 108 è uno pneumatico per ogni tipo di terreno per i veicoli ATV. Il disegno del battistrada assicura comfort e performance eccellenti su strada e fuori strada.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Veicolo ATV



SIZE	Version	USACode	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
AT 20 X 7 - 8	STANDARD	94000555	4	5.5 AT	6.0 AT	6.7	20	0	0	TL	E4-75R-0004980-01
AT 22 X 11 - 8	STANDARD	94000579	4	9.0 AT	8.5 AT	10.9	22	0	0	TL	E4-75R-0004983-01
AT 22 X 10 - 9	STANDARD	94000562	4	8.0 AT	7.5 AT ; 8.5 AT	10	22	0	0	TL	E4-75R-0004982
AT 22 X 11 - 9	STANDARD	94000265	4	9.0 AT	8.5 AT	10.8	21.9	0	0	TL	
AT 22 X 11 - 9	STANDARD	94030019	6	9.0 AT	8.5 AT	10.8	21.9	0	0	TL	E4-75R-0006332
AT 25 X 12 - 9	STANDARD	94000470	4	9.5 AT	9.0 AT ; 10.0 AT	11.5	25.2	0	0	TL	E11-75R-004654
AT 25 X 13 - 9	STANDARD	94000494	4	10.5 AT	10.0 AT	12.6	25	0	0	TL	E11-75R-004655
AT 25 X 13 - 9	STANDARD	94000500	6	10.5 AT	10.0 AT	12.6	25	0	0	TL	E11-75R-004656
AT 20 X 10 - 10	STANDARD	94034499	4	8.0 AT	7.5 AT ; 8.5 AT	9.8	20.2	9.3	56.1	TL	E11-75R-004567
AT 20 X 10 - 10	STANDARD	94052608	8	8.0 AT	7.5 AT ; 8.5 AT	9.8	20.2	9.3	60.1	TL	
AT 22 X 11 - 10	STANDARD	94000210	4	9.0 AT	8.5 AT	10.6	22.2	0	0	TL	E11-75R-005006
AT 22 X 11 - 10	STANDARD	94030002	6	9.0 AT	8.5 AT	10.6	22.2	0	0	TL	E4-75R-0006333
AT 22 X 8 - 10	STANDARD	94000289	4	6.5 AT	6.0 AT	8.1	21.9	0	0	TL	
AT 22 X 8 - 10	STANDARD	94000586	6	6.5 AT	6.0 AT	8.1	21.9	0	0	TL	E4-75R-0004981-01
AT 23 X 10 - 10	STANDARD	94000319	4	8.0 AT	7.5 AT ; 8.5 AT	10.2	23.4	0	0	TL	E11-75R-004658
AT 23 X 8 - 10	STANDARD	94000326	4	6.5 AT	6.0 AT	8.3	23.4	0	0	TL	E11-75R-004659
AT 24 X 11 - 10	STANDARD	94000371	6	9.0	8.5 AT	11.2	23.9	0	0	TL	
AT 24 X 11 - 10	STANDARD	94000593	4	9.0 AT	8.5 AT	11.2	23.9	0	0	TL	E4-75R-0004986
AT 25 X 12 - 10	STANDARD	94000456	4	9.5 AT	9.0 AT ; 10.0 AT	11.7	24.8	0	0	TL	E11-75R-004660
AT 25 X 12 - 10	STANDARD	94000463	6	9.5 AT	9.0 AT ; 10.0 AT	11.7	24.8	0	0	TL	
AT 22 X 7 - 11	STANDARD	94000272	4	5.5 AT		7.1	21.9	0	0	TL	E11-75R-004661
AT 23 X 8 - 11	STANDARD	94000333	4	6.5 AT	6.0 AT	7.5	23.4	0	0	TL	E11-75R-004662
AT 23 X 8 - 11	STANDARD	94000340	6	6.5 AT	6.0 AT	7.5	23.4	0	0	TL	
AT 24 X 10 - 11	STANDARD	94000357	4	8.0 AT	7.5 AT ; 8.5 AT	10	24.2	0	0	TL	E11-75R-004663
AT 24 X 8 - 11	STANDARD	94000388	4	6.5 AT	6.0 AT	8.1	24	0	0	TL	E11-75R-004664
AT 24 X 9 - 11	STANDARD	94000395	4	7.0 AT	7.5 AT	8.7	23.8	0	0	TL	E11-75R-004665
AT 24 X 9 - 11	STANDARD	94000418	6	7.0 AT	7.5 AT	8.7	23.8	0	0	TL	
AT 25 X 10 - 12	STANDARD	94000609	4	8.0 AT	6.5 AT ; 7.5 AT ; 8.5 AT	10	25.2	0	0	TL	E4-75R-0004990
AT 25 X 10 - 12	STANDARD	94000616	6	8.0 AT	6.5 AT ; 7.5 AT ; 8.5 AT	10	25.2	0	0	TL	E4-75R-0004991
AT 25 X 8 - 12	STANDARD	94000623	4	6.5 AT	6.0 AT	8.3	24.8	0	0	TL	E4-75R-0004988
AT 25 X 8 - 12	STANDARD	94000630	6	6.5 AT	6.0 AT	8.3	24.8	0	0	TL	E4-75R-0004989-01

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24/11/2024 02:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..