

AT 110 - Specifiche tecniche



Description

AT 110 è lo pneumatico BKT adatto per applicazioni 4x4 con veicoli ATV. Grazie al suo straordinario controllo di sterzata, AT 110 è lo pneumatico ideale per l'asse anteriore del tuo veicolo.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Veicolo ATV

Version	STANDARD
Type	TL
Tyre Size	AT 23 X 7 - 10

Dimensions US Standard

Usa code	94026838
Ply Rating	4
Section Width (inch)	7
Overall Diameter (inch)	23
Rim Rec	5.5 AT
Rim Alt	6.0 AT
ECE	E4-75R-0006334

Load capacity (lbs)

mph / psi	5
62	240

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 01:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..