

## AT 171 - Scheda tecnica

### Description

AT 171 è stato specificamente progettato per trattori per corse 4x4 nel fango. Il particolare disegno direzionale ed extra profondo del battistrada assicura eccellente trazione su superfici bagnate e fangose.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricoltura: Veicolo ATV • Veicolo per corse nel fango



| SIZE            | Version  | USACode  | TRA Code | LI/SS        | PR | RIM REC | RIM ALT | SW  | OD   | SLR  | RC    | Type |
|-----------------|----------|----------|----------|--------------|----|---------|---------|-----|------|------|-------|------|
| AT 28 X 9 - 14  | STANDARD | 94056866 | R1W+     | 77 A8 / 53 F | 6  | W 7     | W 6     | 8.1 | 28.1 | 0    | 0     | TL   |
| AT 30 X 9 - 14  | STANDARD | 94056873 | R1W+     | 77 A8 / 53 F | 6  | W 7     | W 6     | 8.3 | 29.7 | 0    | 0     | TL   |
| AT 31 X 9 - 16  | STANDARD | 94056842 | R1W+     | 80 A8 / 56 F | 6  | W 7     | W 6     | 8.3 | 30.9 | 0    | 0     | TL   |
| AT 33 X 8 - 18  | STANDARD | 94056835 | R1W+     | 83 A8 / 59 F | 6  | W 6     | W 5.5   | 7.9 | 33.3 | 15.4 | 99.4  | TL   |
| AT 35 X 10 - 18 | STANDARD | 94053780 | R1W+     | 90 A8 / 66 F | 8  | W 8     |         | 9.5 | 35.4 | 16.4 | 104.2 | TT   |
| AT 35 X 10 - 18 | STANDARD | 94055166 | R1W+     | 90 A8 / 66 F | 8  | W 8     |         | 9.5 | 35.4 | 16.4 | 104.2 | TL   |
| AT 33 X 9 - 20  | STANDARD | 94056880 | R1W+     | 85 A8 / 61 F | 6  | W 7     | W 6     | 8.1 | 33   | 15.2 | 103   | TL   |
| AT 35 X 9 - 20  | STANDARD | 94054329 | R1W+     | 85 A8 / 61 F | 6  | W 7     | W 6     | 7.9 | 35.2 | 16.5 | 105.1 | TT   |
| AT 35 X 9 - 20  | STANDARD | 94055173 | R1W+     | 85 A8 / 61 F | 6  | W 7     | W 6     | 7.9 | 35.2 | 16.5 | 105.1 | TL   |
| AT 38 X 10 - 20 | STANDARD | 94054176 | R1W+     | 93 A8 / 69 F | 6  | W 8     | W 7     | 9.3 | 37.4 | 17.4 | 111.6 | TT   |
| AT 38 X 10 - 20 | STANDARD | 94055180 | R1W+     | 93 A8 / 69 F | 6  | W 8     | W 7     | 9.3 | 37.4 | 17.4 | 111.6 | TL   |
| AT 35 X 9 - 22  | STANDARD | 94061587 | R1W+     | 88 A8 / 64 F | 6  | W 7     | W 6     | 8.3 | 35   | 0    | 0     | TL   |
| AT 37 X 9 - 22  | STANDARD | 94054343 | R1W+     | 88 A8 / 64 F | 8  | W 7     | W 6     | 8.1 | 37.2 | 17.5 | 109.4 | TT   |
| AT 37 X 9 - 22  | STANDARD | 94055203 | R1W+     | 88 A8 / 64 F | 8  | W 7     | W 6     | 8.1 | 37.2 | 17.5 | 109.4 | TL   |
| AT 40 X 10 - 22 | STANDARD | 94054183 | R1W+     | 95 A8 / 71 F | 8  | W 8     | W 7     | 9.3 | 39.6 | 18.5 | 116.3 | TT   |
| AT 40 X 10 - 22 | STANDARD | 94055197 | R1W+     | 95 A8 / 71 F | 8  | W 8     | W 7     | 9.3 | 39.6 | 18.5 | 116.3 | TL   |
| AT 40 X 9 - 24  | STANDARD | 94056859 | R1W+     | 90 A8 / 66 F | 8  | W 7     | W 6     | 8.3 | 39.2 | 18.2 | 122.5 | TL   |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 11:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..