

AT 625 - Specifiche tecniche



Description

Progettato per terne e pale compatte, lo pneumatico AT 625 eccelle in tutte le operazioni di coltivazione, di scavo e di carico. È anche la scelta ideale per la raccolta della canna da zucchero, in quanto offre l'affidabilità necessaria per mantenerti produttivo per tutta la stagione. Con il suo battistrada extra profondo, l'AT 625 garantisce una maggiore resistenza alle perforazioni e durata, consentendoti di affrontare condizioni difficili con sicurezza. Questo pneumatico offre una trazione e una stabilità eccezionali, combinate con una maggiore resistenza al taglio e ai trucioli, che lo rendono un partner durevole e affidabile per le tue attività agricole.

UM

US Standard

Construction

❖ BIAS

Machinery

Agricoltura: Mietitrebbia

Industriale: Terna • Pala compatta

Version	INDUSTRIAL
Type	TT
Tyre Size	16.9 - 28
LI/SS	152 A8

Dimensions US Standard

Usa code	94040315
Ply Rating	12
Section Width (inch)	17.7
Overall Diameter (inch)	55.7
Static Loaded Radius (inch)	25.4
Rolling Circumference (inch)	167.5
Rim Rec	DW 15 L
Rim Alt	DW 14 L
TRA Code	R4

Load capacity (lbs)

mph / psi	38
25	7850

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/02/2025 22:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..