

AW 09 - Specifiche tecniche



Description

AW 09 è stato sviluppato per lavorazioni del terreno, la raccolta del fieno e applicazioni di trasporto con attrezzi agricoli, presse per balle di fieno e rimorchi. È idoneo per essere impiegato nell'agricoltura moderna sia su strada che fuori strada. La carcassa rinforzata garantisce un'elevata capacità di carico nonché un ciclo di vita prolungato dello pneumatico. AW 09 è stato sviluppato con una particolare miscela resistente a tagli e lacerazioni che garantisce una straordinaria resistenza alle stoppie.

UM

International Standard

Construction

❖ BIAS

Machinery

Agricoltura: Pressa per balle di fieno • Mietitrebbia •
Attrezzi agricoli • Rimorchio

Version	STANDARD
Type	TL
Tyre Size	260/70 - 15.3
LI/SS DRIVE WHEEL	114 A8
LI/SS FREE ROLLING	126 A8

Dimensions International Standard

Section Width (mm)	268
Overall Diameter (mm)	753
Static Loaded Radius (mm)	335
Rolling Circumference (mm)	2206
Rim Rec	9.00
ECE	E4-106R-000373

Load capacity (Kg)

km/h / bar	3.60
10 FR	2380
25 FR	2025
30 FR	1905
40 FR	1700
10 DW	1650
25 DW	1405
30 DW	1320
40 DW	1180

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 12:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..