

AW 705 - Scheda tecnica



Description

AW 705 è stato sviluppato per attrezzi agricoli, rimorchi e presse per balle di fieno nelle applicazioni per la lavorazione della terra e di trasporto. È idoneo per essere impiegato nell'agricoltura moderna grazie a maggiore durabilità ed elevata capacità di carico.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Pressa per balle di fieno • Attrezzi agricoli •
Rimorchio

SIZE	Version	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
14.0/65 - 16	STANDARD	134 A8	10	11.0		353	870	388	2549	TL	
14.0/65 - 16	STANDARD	142 A8	14	11.0		353	870	388	2549	TL	E4-106R-001901
14.0/65 - 16	STANDARD	142 A8	14	11.0		353	870	388	2549	TT	E4-106R-001901
14.0/65 - 16	STANDARD	134 A8	10	11.0		353	870	388	2549	TT	
15.0/55 - 17	SPECIAL	134 A8	10	13.00	13 ; W 13	381	850	391	2575	TL	E11-106R-004250
15.0/55 - 17	STANDARD	134 A8	10	13.00	13 ; W 13	381	850	391	2575	TL	E4-106R-001546
15.0/55 - 17	STANDARD	138 A8	12	13.00	13 ; W 13	381	850	391	2575	TL	E4-106R-001549
15.0/55 - 17	STANDARD	141 A8	14	13.00	13 ; W 13	381	850	391	2575	TL	E4-106R-001547
15.0/55 - 17	STANDARD	146 A8	18	13.00	13 ; W 13	381	850	391	2575	TL	E4-106R-001882
15.0/55 - 17	STANDARD	155 A8	26	13.00	13 ; W 13	381	850	391	2575	TL	E11-106R-004251
15.0/70 - 18	STANDARD	145 A8	12	13.00	13 ; W 13	405	1010	447	3092	TL	E4-106R-001902
15.0/70 - 18	STANDARD	148 A8	14	13.00	13 ; W 13	405	1010	447	3092	TL	E4-106R-001903
15.0/70 - 18	STANDARD	151 A8	16	13.00	13 ; W 13	405	1010	447	3092	TL	E4-106R-002266
16.0/70 - 20	SPECIAL	154 A8	14	13.0	12 SDC ; 13 SDC ; 14	408	1075	480	3155	TL	E11-106R-004252
16.0/70 - 20	STANDARD	151 A8	12	13.0	12 SDC ; 13 SDC ; 14	408	1075	480	3155	TT	E4-106R-002711
16.0/70 - 20	STANDARD	151 A8	12	13.0	12 SDC ; 13 SDC ; 14	414	1085	483	3342	TL	E4-106R-002711
16.0/70 - 20	STANDARD	154 A8	14	13.0	12 SDC ; 13 SDC ; 14	408	1075	480	3155	TT	E11-106R-003368
16.0/70 - 20	STANDARD	154 A8	14	13.0	12 SDC ; 13 SDC ; 14	408	1075	480	3155	TL	E11-106R-003368
16.0/70 - 20	STANDARD	156 A8	16	13.0	12 SDC ; 13 SDC ; 14	408	1075	480	3155	TL	E4-106R-002267
400/55 - 22.5	STANDARD	154 A8	18	AG 11.75	12.25 ; AG 13.00	405	1016	443	3072	TL	E11-106R-004550
400/55 - 22.5	STUBBLE RESISTANT	156 A8	20	AG 11.75	12.25 ; AG 13.00	405	1016	443	3072	TL	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24/11/2024 03:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..