

AW 705 - Scheda tecnica



Description

AW 705 è stato sviluppato per attrezzi agricoli, rimorchi e presse per balle di fieno nelle applicazioni per la lavorazione della terra e di trasporto. È idoneo per essere impiegato nell'agricoltura moderna grazie a maggiore durabilità ed elevata capacità di carico.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Pressa per balle di fieno • Attrezzi agricoli •
Rimorchio

SIZE	Version	USACode	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
14.0/65 - 16	STANDARD	94009916	134 A8	10	11.0		13.9	34.3	15.3	100.4	TL	
14.0/65 - 16	STANDARD	94009930	142 A8	14	11.0		13.9	34.3	15.3	100.4	TL	E4-106R-001901
14.0/65 - 16	STANDARD	94009923	142 A8	14	11.0		13.9	34.3	15.3	100.4	TT	E4-106R-001901
14.0/65 - 16	STANDARD	94009909	134 A8	10	11.0		13.9	34.3	15.3	100.4	TT	
15.0/55 - 17	SPECIAL	94048335	134 A8	10	13.00	13 ; W 13	15	33.5	15.4	101.4	TL	E11-106R-004250
15.0/55 - 17	STANDARD	94009978	134 A8	10	13.00	13 ; W 13	15	33.5	15.4	101.4	TL	E4-106R-001546
15.0/55 - 17	STANDARD	94010028	138 A8	12	13.00	13 ; W 13	15	33.5	15.4	101.4	TL	E4-106R-001549
15.0/55 - 17	STANDARD	94010066	141 A8	14	13.00	13 ; W 13	15	33.5	15.4	101.4	TL	E4-106R-001547
15.0/55 - 17	STANDARD	94010097	146 A8	18	13.00	13 ; W 13	15	33.5	15.4	101.4	TL	E4-106R-001882
15.0/55 - 17	STANDARD	94054022	155 A8	26	13.00	13 ; W 13	15	33.5	15.4	101.4	TL	E11-106R-004251
15.0/70 - 18	STANDARD	94010110	145 A8	12	13.00	13 ; W 13	15.9	39.8	17.6	121.7	TL	E4-106R-001902
15.0/70 - 18	STANDARD	94010158	148 A8	14	13.00	13 ; W 13	15.9	39.8	17.6	121.7	TL	E4-106R-001903
15.0/70 - 18	STANDARD	94025749	151 A8	16	13.00	13 ; W 13	15.9	39.8	17.6	121.7	TL	E4-106R-002266
16.0/70 - 20	SPECIAL	94029884	154 A8	14	13.0	12 SDC ; 13 SDC ; 14	16.1	42.3	18.9	124.2	TL	E11-106R-004252
16.0/70 - 20	STANDARD	94010189	151 A8	12	13.0	12 SDC ; 13 SDC ; 14	16.1	42.3	18.9	124.2	TT	E4-106R-002711
16.0/70 - 20	STANDARD	94027408	151 A8	12	13.0	12 SDC ; 13 SDC ; 14	16.3	42.7	19	131.6	TL	E4-106R-002711
16.0/70 - 20	STANDARD	94010202	154 A8	14	13.0	12 SDC ; 13 SDC ; 14	16.1	42.3	18.9	124.2	TT	E11-106R-003368
16.0/70 - 20	STANDARD	94026227	154 A8	14	13.0	12 SDC ; 13 SDC ; 14	16.1	42.3	18.9	124.2	TL	E11-106R-003368
16.0/70 - 20	STANDARD	94010219	156 A8	16	13.0	12 SDC ; 13 SDC ; 14	16.1	42.3	18.9	124.2	TL	E4-106R-002267
400/55 - 22.5	STANDARD	94042449	154 A8	18	AG 11.75	12.25 ; AG 13.00	15.9	40	17.4	120.9	TL	E11-106R-004550
400/55 - 22.5	STUBBLE RESISTANT	94060306	156 A8	20	AG 11.75	12.25 ; AG 13.00	15.9	40	17.4	120.9	TL	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24/11/2024 03:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..