

AW 708 - Specifiche tecniche

Description

AW 708 è stato sviluppato per la lavorazione della terra nonché applicazioni di trasporto e raccolta del fieno con attrezzi agricoli, rimorchi e macchine per la raccolta del fieno/pressapaglia. È disponibile una versione "HD" con mescola speciale resistente a tagli e lacerazioni.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Pressa per balle di fieno • Attrezzi agricoli •
Rimorchio
Industriale: Rimorchio



Version	STANDARD
Type	TL
Tyre Size	500/65 - 17
LI/SS FREE ROLLING	160 A8

Dimensions US Standard

Usa code	94034307
Ply Rating	18
Section Width (inch)	20.7
Overall Diameter (inch)	42.5
Static Loaded Radius (inch)	18.2
Rolling Circumference (inch)	123.4
Rim Rec	16.0
ECE	E11-106R-004549

Load capacity (lbs)

mph / psi	51
5 FR	13890
15 FR	11810
20 FR	11110
25 FR	9920

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24/11/2024 00:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..