

BK 208 - Scheda tecnica



Description

BK 208è idoneo per applicazioni con rimorchi e camioncini. È uno pneumatico notevolmente durevole ed affidabile per impieghi sia su campo che sulla strada.

UM

International Standard

Construction



Machinery

Agricoltura: Trattore compatto • Autocarro leggero • Rimorchio

SIZE	Version	PR	RIM REC	RIM ALT	SW	OD	Туре
7.50 - 16	STANDARD	12	6.00 G		212	810	TT
7.50 - 16	STANDARD	14	6.00 G		212	810	TT
7.50 - 16	STANDARD	16	6.00 G		212	810	TT

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 02:32

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..