

## BK 308 - Specifiche tecniche



### Description

BK 308 è stato particolarmente sviluppato per rimorchi e trattori compatti. Lo pneumatico si distingue per l'eccellente trazione su tutte le superfici e elementi intermedi (tie bar) tra i tasselli del battistrada per ridurre l'effetto di crepe di sforzo nel battistrada. La carcassa robusta realizzata con una miscela speciale del battistrada offre eccellente durabilità e ottima resistenza contro la foratura per assicurare una vita operativa più estesa.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricoltura: Trattore compatto • Rimorchio

Version	STANDARD
Type	TT
Tyre Size	6.50 - 20
LI/SS	112 A6

## Dimensions International Standard

Ply Rating	10
Section Width (mm)	190
Overall Diameter (mm)	865
Rim Rec	5.50 F
Rim Alt	4.00 E ; 5.00 F
ECE	E11-106R-003563

## Load capacity (Kg)

km/h / bar	4.8
30	1120

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24/11/2024 03:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..