

## BK 823 - Specifiche tecniche



### Description

BK 823 è uno pneumatico progettato per trattori, attrezzi agricoli e rimorchi nelle applicazioni di lavorazione del terreno e di trasporto sia su campo che su strada. Lo speciale disegno a blocchi del battistrada, lo rende particolarmente idoneo per impieghi pesanti in cui ottime prestazioni di sterzata sono un requisito essenziale. È disponibile anche una versione HD con resistenza a tagli e lacerazioni avanzate.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricoltura: Attrezzi agricoli • Trattore • Rimorchio

Version	STANDARD
Type	TL
Tyre Size	9.00 - 16
LI/SS	121 A8

## Dimensions US Standard

Usa code	94060252
Ply Rating	10
Section Width (inch)	9.6
Overall Diameter (inch)	35.1
Static Loaded Radius (inch)	15.5
Rolling Circumference (inch)	101.7
Rim Rec	6.5

## Load capacity (lbs)

mph / psi	46
25	3200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 22:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..