

COMMANDER (F) - Specifiche tecniche



Description

COMMANDER (F) è uno pneumatico con nervatura del battistrada a 3 costole – perfetto per la lavorazione del terreno e applicazioni di trasporto. Il battistrada profondo è realizzato con una miscela particolarmente resistente ad ogni tipo di taglio per una lunga vita dello pneumatico assicurando altresì un'elevata capacità di carico.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Trattore 2WD

Version	STANDARD
Type	TT
Tyre Size	6.50 - 16
LI/SS	102 A6

Dimensions International Standard

Ply Rating	10
TKPH	1
Section Width (mm)	183
Overall Diameter (mm)	770
Static Loaded Radius (mm)	362
Rolling Circumference (mm)	2332
Rim Rec	4.50 E
Rim Alt	4.00 E ; 5.00 F ; 5.50 F
ECE	E11-106R-004109
TRA Code	F2

Load capacity (Kg)

	km/h / bar	5.00
	30	850

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 12:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..