

COMMANDER (F) - Scheda tecnica



Description

COMMANDER (F) è uno pneumatico con nervatura del battistrada a 3 costole – perfetto per la lavorazione del terreno e applicazioni di trasporto. Il battistrada profondo è realizzato con una mescola particolarmente resistente ad ogni tipo di taglio per una lunga vita dello pneumatico assicurando altresì un'elevata capacità di carico.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Trattore 2WD

SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	TMPH	ECE
5.50 - 16	STANDARD	94052806	F2	78 A8	6	4.00 E	3.50D ; 4.50E	6.1	28.3	13.4	84.4	TT	1	E11-106R-003308
6.00 - 16	STANDARD	94045150	F2	91 A8	8	4.50 E	4.00 E ; 5.00 F	6.9	29.5	14.1	90.9	TT	0	E11-106R-003001
6.50 - 16	STANDARD	94045402	F2	90 A8	8	4.50 E	4.00 E ; 5.00 F ; 5.50 F	7.2	30.3	14.3	91.8	TT	1	E11-106R-004107
6.50 - 16	STANDARD	94051809	F2	95 A8	10	4.50 E	4.00 E ; 5.00 F ; 5.50 F	7.2	30.3	14.3	91.8	TT	1	E11-106R-004109
7.50 - 16	STANDARD	94050703	F2	99 A8	8	5.50 F	5.00 F ; 5 K ; 6.00 F	8.3	31.9	14.8	95.8	TT	1	E11-106R-004116

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 11:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..