

## COMMANDER (R) - Scheda tecnica



### Description

COMMANDER (R) è uno pneumatico agricoltura caratterizzato da un battistrada profondo con una base forte dei tasselli che assicurano un ciclo di vita prolungato dello pneumatico. Lo speciale disegno dei tasselli a due angolazioni garantisce sia un'eccellente trazione sul campo che ottime qualità di autopulitura. La robusta carcassa è realizzata con una miscela particolarmente resistente ad ogni tipo di taglio che fornisce una migliore resistenza alla perforazione nonché elevata capacità di carico. COMMANDER (R) è lo pneumatico perfetto per la lavorazione del terreno nonché le operazioni di trasporto e di raccolto.

### UM

US Standard

### Construction

BIAS

### Machinery

Agricoltura: Mietitrebbia • Trattore

SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	TMPH	ECE
9.5 - 20	STANDARD	94058921	R1	105 A8	12	W 8	W 7	9.6	38.2	18	116.1	TT	1	E11-106R-005246
11.2 - 24	STANDARD	94054367	R1	120 A8	12	W 10	W 9	11.6	44.3	21	137.1	TT	0	E11-106R-004616
12.4 - 24	STANDARD	94052745	R1	124 A8	12	W 11	W 10	12.9	46.5	22.4	144.4	TT	1	E11-106R-004365
12.4 - 24	STANDARD	94057924	R1	117 A8	8	W 11	W 10	12.9	46.5	22.4	144.4	TT	1	E11-106R-005208
9.5 - 24	STANDARD	94052912	R1	110 A8	12	W8	W 7	9.6	41.9	20	130.2	TT	1	E11-106R-004364
12.4 - 28	STANDARD	94045846	R1	121 A8	12	W 11	W 9 ; W 10	12.6	50.6	23.6	155.4	TT	1	E11-106R-002999
13.6 - 28	STANDARD	94045136	R1	124 A8	12	W 12	W 11	14.2	53	24.5	160.2	TT	1	E11-106R-003002
14.9 - 28	STANDARD	94048021	R1	130 A8	12	W 13	W 11 , W 12	15.3	54.3	25.3	164.4	TT	1	E11-106R-005966
15.9 - 28	STANDARD	94075591	R1	136 A8	12	W 13	W 11 , W 12	15.9	55.5	0	0	TT	0	E11-106R-009016
16.9 - 28	STANDARD	94048212	R1	139 A8	12	W 15 L	W 14 L	17.3	56.5	26.1	168.3	TT	1	E11-106R-003627
16.9 - 28 (21L)	STANDARD	94075584	R1	139 A8	12	W 15 L	W 14 L	17.3	56.5	0	0	TT	0	E11-106R-009015
17.9 - 28	STANDARD	94073214	R1	140 A8	12	W 15 L	W 14 L	18	59.6	0	0	TT	1	E11-106R-007701
16.9 - 30	STANDARD	94067640	R1	140 A8	12	W 15 L	W 14 L	17.3	58.3	27.1	178.6	TT	0	E11-106R-006618
18.4 - 30	STANDARD	94051502	R1	145 A8	14	W 16 L		18.6	61.6	28.9	190.3	TT	1	E11-106R-004525
18.4 - 30	STANDARD	94052752	R1	151 A8	18	W 16 L		18.6	61.6	28.9	190.3	TT	1	E11-106R-004368
18.4 - 30	STANDARD	94052844	R1	151 A8	18	W 16 L		18.6	61.6	28.9	190.3	TL	1	E11-106R-004368
18.4 - 30	STANDARD	94057931	R1	135 A8	8	W 16 L		18.6	61.6	28.9	190.3	TT	1	E11-106R-005247
9.5 - 36	STANDARD	94073566	R1	122 A8	12	W 8	W 7	9.7	54.2	0	0	TT	0	E11-106R-007809

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 10:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..