

## COMMANDER TWIN RIB - Scheda tecnica



### Description

COMMANDER TWIN RIB è uno pneumatico con nervatura del battistrada a 4 costole e dentellature sulle spalle che assicura ottima aderenza. La resistente zona contrafforte offre un'eccellente protezione dei fianchi, mentre il profilo più largo del battistrada garantisce un'ottima distribuzione del peso.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricoltura: Trattore 2WD

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	Type	TKPH	ECE
5.00 - 15	STANDARD	F2	82 A6	6	4.00 E		145	665	TT	1	
6.00 - 16	STANDARD	F2	94 A6	8	4.50 E	4.00 E ; 5.00 F	170	750	TT	0	E11-106R-004091
6.50 - 16	STANDARD	F2	98 A6	8	4.50 E	4.00 E ; 5.00 F ; 5.50 F	180	761	TT		E11-106R-004107
7.50 - 16	STANDARD	F2	103 A6	8	5.50 F	5.00 F ; 5 K ; 6.00 F	210	810	TT		E11-106R-006953
6.50 - 20	STANDARD	F2	101 A6	8	5.00 F	4.00 E ; 5.50 F	190	875	TT	1	E11-106R-004258

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24/11/2024 03:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..