

COMMANDER TWIN RIB - Scheda tecnica



Description

COMMANDER TWIN RIB è uno pneumatico con nervatura del battistrada a 4 costole e dentellature sulle spalle che assicura ottima aderenza. La resistente zona contrafforte offre un'eccellente protezione dei fianchi, mentre il profilo più largo del battistrada garantisce un'ottima distribuzione del peso.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Trattore 2WD

SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	Type	TMPH	ECE
5.00 - 15	STANDARD	94059669	F2	76 A8	6	4.00 E		5.7	26.2	TT	1	
6.00 - 16	STANDARD	94045167	F2	91 A8	8	4.50 E	4.00 E ; 5.00 F	6.7	29.5	TT	0	E11-106R-004091
6.50 - 16	STANDARD	94064618	F2	90 A8	8	4.50 E	4.00 E ; 5.00 F ; 5.50 F	7.1	30	TT	0	E11-106R-004107
7.50 - 16	STANDARD	94058235	F2	99 A8	8	5.50 F	5.00 F ; 5 K ; 6.00 F	8.3	31.9	TT	0	E11-106R-006953
6.50 - 20	STANDARD	94054015	F2	93 A8	8	5.00 F	4.00 E ; 5.50 F	7.5	34.4	TT	1	E11-106R-004258

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24/11/2024 03:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..