

## CON STAR - Specifiche tecniche



### Description

CON STAR è particolarmente idoneo per pale compatte e sollevatori telescopici nelle applicazioni agro-industriali, di sollevamento e di carico. Lo pneumatico è caratterizzato da un'ottima trazione abbinata ad una stabilità eccellente verticale ed orizzontale. CON STAR è stato realizzato con una mescola particolarmente resistente ad ogni tipo di taglio che contribuisce ad un ciclo di vita prolungato dello pneumatico.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricoltura: Pala compatta • Sollevatore telescopico  
Industriale: Pala compatta • Sollevatore telescopico

Version	INDUSTRIAL
Type	TL
Tyre Size	400/70 - 20 (16.0/70 - 20)
LI/SS	156 A8

## Dimensions International Standard

Section Width (mm)	405
Overall Diameter (mm)	1080
Static Loaded Radius (mm)	501
Rolling Circumference (mm)	3303
SRI (mm)	525
Rim Rec	13
Rim Alt	12 SDC ; 13 SDC ; 14
ECE	E11-106R-003023

## Load capacity (Kg)

km/h / bar	5.00
40	4000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24/11/2024 01:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..