

CON STAR - Specifiche tecniche



Description

CON STAR è particolarmente idoneo per pale compatte e sollevatori telescopici nelle applicazioni agro-industriali, di sollevamento e di carico. Lo pneumatico è caratterizzato da un'ottima trazione abbinata ad una stabilità eccellente verticale ed orizzontale. CON STAR è stato realizzato con una mescola particolarmente resistente ad ogni tipo di taglio che contribuisce ad un ciclo di vita prolungato dello pneumatico.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Pala compatta • Sollevatore telescopico
Industriale: Pala compatta • Sollevatore telescopico

Version	INDUSTRIAL
Type	TL
Tyre Size	400/70 - 24 (16.0/70 - 24)
LI/SS	158 A8

Dimensions International Standard

Section Width (mm)	395
Overall Diameter (mm)	1175
Static Loaded Radius (mm)	544
Rolling Circumference (mm)	3556
SRI (mm)	575
Rim Rec	13
Rim Alt	DW 12 ; 13 SDC ; DW 13 ; DW 13 L ; DW 14 L
ECE	E11-106R-003025

Load capacity (Kg)

km/h / bar	5.00
40	4250

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24/11/2024 01:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..