

## CON STAR - Scheda tecnica



### Description

CON STAR è particolarmente idoneo per pale compatte e sollevatori telescopici nelle applicazioni agro-industriali, di sollevamento e di carico. Lo pneumatico è caratterizzato da un'ottima trazione abbinata ad una stabilità eccellente verticale ed orizzontale. CON STAR è stato realizzato con una mescola particolarmente resistente ad ogni tipo di taglio che contribuisce ad un ciclo di vita prolungato dello pneumatico.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricoltura: Pala compatta • Sollevatore telescopico  
Industriale: Pala compatta • Sollevatore telescopico

SIZE	Version	USACode	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
<b>340/80 - 18</b> (12.5/80 - 18)	INDUSTRIAL	94051304	143 A8		11	12 ; 11 SDC ; 12 SDC ; W 10 ; W 11	13.8	40	18.3	119.7	TL	E11-106R-003020
<b>340/80 - 20</b> (12.5/80 - 20)	INDUSTRIAL	94051311	144 A8		11	12 ; 11 SDC ; 12 SDC ; W 10 ; W 11	13.8	41.9	19.3	128.8	TL	E11-106R-003021
<b>380/75 - 20</b> (14.5 - 20)	INDUSTRIAL	94051519	148 A8		W 12	W 11 ; 12 SDC ; 12 ; W 13 ; 13 SDC ; 13	15.2	42.5	19.7	128.9	TL	E11-106R-003022
<b>400/70 - 20</b> (16.0/70 - 20)	INDUSTRIAL	94043323	149 A8	16	13	12 SDC ; 13 SDC ; 14	15.9	42.5	19.7	130	TL	E11-106R-003024
<b>400/70 - 20</b> (16.0/70 - 20)	INDUSTRIAL	94051823	156 A8		13	12 SDC ; 13 SDC ; 14	15.9	42.5	19.7	130	TL	E11-106R-003023
<b>400/70 - 24</b> (16.0/70 - 24)	INDUSTRIAL	94051977	158 A8		13	DW 12 ; 13 SDC ; DW 13 ; DW 13 L ; DW 14 L	15.6	46.3	21.4	140	TL	E11-106R-003025
<b>400/80 - 24</b> (15.5/80 - 24)	INDUSTRIAL	94040599	162 A8	20	DW 13	DW 12 ; DW 13 L ; DW 14 L	15.9	49.2	22.4	148.9	TL	E11-106R-003026
<b>440/80 - 24</b> (17.0/80 - 24)	INDUSTRIAL	94042067	168 A8	22	DW 14 L	DW 13 ; DW 13 L ; DW 15 L	17.9	51.8	24	156.9	TL	E11-106R-003027
<b>460/70 - 24</b> (17.5L - 24)	INDUSTRIAL	94052424	159 A8		DW 15 L	DW 14 L ; DW 16 L	18.1	49.2	22.1	149	TL	E11-106R-003029
<b>500/70 - 24</b> (19.5L - 24)	INDUSTRIAL	94051731	164 A8		DW 16 L	DW 15 L ; DW 18 L	19.9	51.2	22.8	154.6	TL	E11-106R-003031
<b>480/80 - 26</b> (18.4 - 26)	INDUSTRIAL	94052813	160 A8		DW 15 L	DW 16 L	19.3	55.5	25.3	168.2	TL	E11-106R-003033
<b>440/80 - 28</b> (16.9 - 28)	INDUSTRIAL	94051199	156 A8		DW 14 L	DW 13 ; DW 13 L ; DW 15 L	17.7	55.9	24.9	169.3	TL	E11-106R-003035

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24/11/2024 01:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..