

DON 2000 - Specifiche tecniche



Description

DON 2000 è uno pneumatico idoneo per operazioni di trasporto con rimorchi e camioncini sia su strada che fuori strada. Assicura straordinaria durabilità abbinata ad elevate performance durante l'intero ciclo di vita del prodotto.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Autocarro leggero • Rimorchio

| | |
|-----------|--------------------|
| Version | INDUSTRIAL TRAILER |
| Type | TT |
| Tyre Size | 10.00 - 20 |

Dimensions International Standard

| | |
|------------------------------|-----------|
| Ply Rating | 16 |
| Section Width (mm) | 286 |
| Overall Diameter (mm) | 1080 |
| Rim Rec | 7.5 |
| Rim Alt | 7.0 ; 8.0 |

Load capacity (Kg)

| | km/h / bar | 8.75 | 8.00 |
|-------|------------|------|------|
| 40 LS | | 3450 | - |
| 40 LD | | - | 3050 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 15:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..