

DON 2000 - Scheda tecnica



Description

DON 2000 è uno pneumatico idoneo per operazioni di trasporto con rimorchi e camioncini sia su strada che fuori strada. Assicura straordinaria durabilità abbinata ad elevate performance durante l'intero ciclo di vita del prodotto.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Autocarro leggero • Rimorchio

SIZE	Version	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type
7.50 - 16	STANDARD	16	6.00 G	5.50 F	216	840	0	0	TT
10.00 - 20	INDUSTRIAL TRAILER	16	7.5	7.0 ; 8.0	286	1080	0	0	TT
10.00 - 20	INDUSTRIAL TRAILER	18	7.5	7.0 ; 8.0	286	1080	0	0	TT
11.00 - 20	STANDARD	18	8.0	7.5 ; 8.5	292	1110	520	3414	TT
12.00 - 20	STANDARD	18	8.5	8.0 ; 9.0	315	1145	535	3519	TT
9.00 - 20	STANDARD	16	7.0	6.5 ; 7.5	270	1048	0	0	TT
9.00 - 20	TRACTOR TRAILER	16	7.0	6.5 ; 7.5	270	1048	0	0	TT
12.00 - 24	STANDARD	18	8.5	8.0 ; 9.0	315	1245	0	0	TT

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 13:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..