

EARTHMAX SR 30 - Specifiche tecniche



Description

EARTHMAX SR 30 (E-3/L-3) è uno pneumatico radiale All Steel progettato per il duplice impiego con loader o dumper articolati. Le cinture d'acciaio multistrato e il disegno rigido a blocchi assicurano trazione, stabilità e durabilità eccellenti. La speciale miscela resistente al taglio rende EARTHMAX SR 30 la soluzione ideale per una varietà di condizioni operative dure.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Dumper articolato • Dozer • Pala caricatrice

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	15.5 R 25
LI/SS	160 B/169 A2

Dimensions International Standard

TKPH	130
Overall Width (mm)	397
Overall Diameter (mm)	1276
Static Loaded Radius (mm)	574
Rolling Circumference (mm)	3809
Rim Rec	12.00/1.3
Rim Alt	-
Star Rating	**/*
TRA Code	E3/L3

Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75	5.00	5.25
50	3650	3875	4000	4250	4375	4500
10	5000	5150	5450	5600	5800	-

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/11/2024 21:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..