

EARTHMAX SR 31 - Specifiche tecniche



Description

EARTHMAX SR 31 è uno pneumatico radiale All Steel progettato per dumper rigidi e pale gommate. Le cinture in acciaio multistrato assicurano forza e stabilità straordinarie, mentre il disegno non-direzionale rigido a blocchi garantisce trazione e manovrabilità eccellenti, anche su fondo fangoso. Oltre allo straordinario comfort di guida, EARTHMAX SR 31 si distingue anche per una miscela speciale del battistrada, particolarmente resistente ai tagli e al calore. La struttura radiale della carcassa offre inoltre una bassa resistenza al rotolamento con conseguenti risparmi significativi di carburante.

UM

International Standard

Construction

 RADIAL

Machinery

Industriale: Dozer • Pala caricatrice

OTR: Dumper articolato • Dozer • Pala caricatrice

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	20.5 R 25
LI/SS	177 B/186 A2

Dimensions International Standard

TKPH	170
Overall Width (mm)	540
Overall Diameter (mm)	1480
Static Loaded Radius (mm)	663
Rolling Circumference (mm)	4449
Rim Rec	17.00/2.0
Rim Alt	--
Star Rating	**/*
TRA Code	E3/L3

Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75	5.00	5.25
50	5800	6150	6500	6700	6900	7300
10	8000	8250	8750	9000	9500	-

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 06:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..