

EARTHMAX SR 412 - Specifiche tecniche



Description

EARTHMAX SR 412 (E-4/L-4) è uno pneumatico radiale All Steel particolarmente progettato per dumper articolati, loader e dozer. Il disegno unico del battistrada con profondità E-4 assicura eccellente trazione e straordinaria resistenza al calore. Grazie alla robusta carcassa e le cinture All Steel, EARTHMAX SR 412 è in grado di trasportare carichi pesanti, garantendo eccezionale stabilità nonché resistenza a lacerazioni e forature. La spalla di forma quadrata di EARTHMAX SR 412 offre massimo contatto con il terreno e quindi eccellente manovrabilità.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Dumper articolato • Dozer • Pala caricatrice

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	800/65 R 29
LI/SS	198 B / 208 A2

Dimensions US Standard

Usa code	94070572
TMPH	141
Overall Width (inch)	31.1
Overall Diameter (inch)	71.1
Static Loaded Radius (inch)	32.5
Rolling Circumference (inch)	216.1
Rim Rec	27.00/3.0
Rim Alt	24.00/3.5 , 25.00/3.5
Star Rating	**/*
TRA Code	E4/L4

Load capacity (lbs)

mph / psi	58	62	65	69
30	26000	26800	28300	29100
5	35300	36400	37500	39700

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24/11/2024 02:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..