

EARTHMAX SR 412 - Scheda tecnica



Description

EARTHMAX SR 412 (E-4/L-4) è uno pneumatico radiale All Steel particolarmente progettato per dumper articolati, loader e dozer. Il disegno unico del battistrada con profondità E-4 assicura eccellente trazione e straordinaria resistenza al calore. Grazie alla robusta carcassa e le cinture All Steel, EARTHMAX SR 412 è in grado di trasportare carichi pesanti, garantendo eccezionale stabilità nonché resistenza a lacerazioni e forature. La spalla di forma quadrata di EARTHMAX SR 412 offre massimo contatto con il terreno e quindi eccellente manovrabilità.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Dumper articolato • Dozer • Pala caricatrice

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TMPH
29.5 R 25	CUT RESISTANT COMPOUND	94062836	E4	**	200 B	25.00/3.5		30.1	73.4	32.8	218.2	TL	173
750/65 R 25 (30/65 R 25)	CUT RESISTANT COMPOUND	94065233	E4/L4	**/*	190 B/202 A2	24.00/3.0	22.00/3.0, 25.00/3.0	30.7	63.1	28.1	190.5	TL	157
750/65 R 25 (30/65 R 25)	CUT RESISTANT COMPOUND	94064144	E4	**	190 B	24.00/3.0	22.00/3.0; 25.00/3.0	30.7	63.1	28.1	190.5	TL	157
800/65 R 29	CUT RESISTANT COMPOUND	94070572	E4/L4	**/*	198 B / 208 A2	27.00/3.0	24.00/3.5, 25.00/3.5	31.1	71.1	32.5	216.1	TL	141

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24/11/2024 02:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..