

EARTHMAX SR 45 M - Specifiche tecniche

Description

EARTHMAX SR 45 M è uno pneumatico radiale **All Steel** particolarmente progettato per dumper rigidi. EARTHMAX SR 45 M assicura ottima trazione ed è ideale per operazioni su lunghe distanze.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Dumper rigido



Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	18.00 R 33
LI/SS	195 B

Dimensions US Standard

Usa code	94513888
TMPH	127
Overall Width (inch)	19.9
Overall Diameter (inch)	73.6
Static Loaded Radius (inch)	33.7
Rolling Circumference (inch)	220.8
Rim Rec	13.00/2.5
Star Rating	***
TRA Code	E4
Tread Depth	69

Load capacity (lbs)

mph / psi	105	109	112	116
30	24700	25400	26000	26800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/03/2025 12:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..