

## EARTHMAX SR 454 - Specifiche tecniche



### Description

EARTHMAX SR 454 è uno pneumatico radiale All Steel specificamente progettato per camion rigidi da trasporto. L'esclusivo design del battistrada E-3 e la speciale scanalatura centrale forniscono trazioni laterali ottimizzate e una migliore maneggevolezza sia su superfici morbide che fangose. Questo pneumatico è stato appositamente progettato per consentire velocità più elevate e lunghi viaggi a temperature di esercizio più basse. La costruzione All Steel con cinghie in acciaio multistrato offre una protezione superiore contro urti e penetrazione di frammenti di rocce, per migliorare i tempi di attività con la conseguenza di una maggiore produttività. La spalla quadrata di EARTHMAX SR 454 massimizza il contatto con il suolo per una manovrabilità e una stabilità eccellenti, oltre a vibrazioni e rumore ridotti al minimo.

### UM

International Standard

### Construction

 RADIAL

### Machinery

OTR: Dumper rigido

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	40.00 R 57
LI/SS	250 B

## Dimensions International Standard

TKPH	1201
Overall Width (mm)	1115
Overall Diameter (mm)	3510
Static Loaded Radius (mm)	1583
Rolling Circumference (mm)	10654
Rim Rec	29.00/6.0
Rim Alt	32.00/6.0
Star Rating	**
TRA Code	E3

## Load capacity (Kg)

km/h / bar	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	50000	51500	53000	54500	56000	58000	60000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 16:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..