

## EARTHMAX SR 475 - Specifiche tecniche



### Description

EARTHMAX SR 475 è uno pneumatico radiale All Steel particolarmente progettato per dumper rigidi. È ideale per operazioni in ambienti duri e rocciosi e per trasporti lunghi. Il disegno unico del battistrada genera meno calore nei climi caldi e assicura trazione eccellente. La sua carcassa All Steel e le cinture garantiscono straordinaria stabilità e resistenza a tagli e perforazioni. EARTHMAX SR 475 è stato sviluppato con una spalla quadrata che assicura eccellente manovrabilità, ottimizzando il contatto sul terreno.

### UM

International Standard

### Construction

 RADIAL

### Machinery

OTR: Dumper rigido

Version	STANDARD COMPOUND
Type	TL
Tyre Size	24.00 R 35
LI/SS	209 B

## Dimensions International Standard

TKPH	422
Overall Width (mm)	654
Overall Diameter (mm)	2160
Static Loaded Radius (mm)	971
Rolling Circumference (mm)	6589
Rim Rec	17.00/3.5
Star Rating	**
TRA Code	E4

## Load capacity (Kg)

km/h / bar	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	14000	14500	15500	16000	16500	17000	17500	18000	18500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 10:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..