

## EARTHMAX SR 48 - Scheda tecnica



### Description

EARTHMAX SR 48 è uno pneumatico All Steel specificamente sviluppato per dumper rigidi. Questo pneumatico assicura maggiore trazione e straordinaria resistenza all'usura anche nelle operazioni più ardue in ambienti rocciosi. È ideale per il trasporto di carichi pesanti. La spalla di forma quadrata protegge il fianco da tagli e danni. EARTHMAX SR 48 mostra una robusta carcassa All Steel che offre eccezionale protezione contro urti e perforazioni di sassi ottimizzando la produttività.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Dumper rigido

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TMPH
24.00 R 35	CUT RESISTANT COMPOUND	94060276	E4	**	209 B	17.00/3.5		26.2	85.8	39.1	260.7	TL	212
24.00 R 35	STANDARD COMPOUND	94059713	E4	**	209 B	17.00/3.5		26.2	85.8	39.1	260.7	TL	258
27.00 R 49	CUT RESISTANT COMPOUND	94053209	E4	**	223 B	19.50/4.0	--	29.1	105.8	48.2	321.5	TL	301
27.00 R 49	HEAT RESISTANT COMPOUND	94054312	E4	**	223 B	19.50/4.0	--	29.1	105.8	48.2	321.5	TL	411
27.00 R 49	STANDARD COMPOUND	94055142	E4	**	223 B	19.50/4.0	--	29.1	105.8	48.2	321.5	TL	349

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 12:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..