

## EARTHMAX SR 55 - Specifiche tecniche



### Description

EARTHMAX SR 55 è uno pneumatico radiale All Steel specialmente progettato per loader, dozer e pale LHD che operano nelle condizioni più severe come nelle cave e miniere, nonché nei cantieri di demolizione. Grazie al disegno del battistrada extra profondo e liscio EARTHMAX SR 55 è in grado di raggiungere elevati picchi di produttività con minori tempi di fermo macchina, assicurando ottima durabilità. Gli operatori delle macchine apprezzeranno anche stabilità e trazione straordinarie.

### UM

International Standard

### Construction

 RADIAL

### Machinery

OTR: Dozer • Pala LHD • Pala caricatrice

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	35/65 R 33
LI/SS	224 A2

## Dimensions International Standard

Overall Width (mm)	900
Overall Diameter (mm)	2065
Static Loaded Radius (mm)	915
Rolling Circumference (mm)	6175
Rim Rec	28.00/3.5
Rim Alt	--
Star Rating	**
TRA Code	L5S

## Load capacity (Kg)

km/h / bar	5.25	5.50	5.75	6.00	6.25	6.50
10	23600	25000	25750	26500	27250	28000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 11:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..