

## EM 933 SUPER - Specifiche tecniche



### Description

EM 933 SUPER è stato appositamente progettato per gli scavatori in operazioni di scavo e di carico. L'eccezionale design del fianco con una nervatura sporgente del cordolo consente uno stretto contatto tra due pneumatici, eliminando la necessità di un anello di gomma speciale per impedire la penetrazione di pietre. L'esclusivo disegno del battistrada garantisce una trazione superiore in condizioni di servizio gravose. Altre caratteristiche dell'EM 933 SUPER sono l'eccezionale comfort di guida e le proprietà autopulenti.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industriale: Escavatore

Version	STANDARD
Type	TT
Tyre Size	290/90 - 20
LI/SS	152 B / 168 A2

## Dimensions International Standard

<b>Ply Rating</b>	18
<b>Overall Width (mm)</b>	295
<b>Overall Diameter (mm)</b>	1055
<b>Rim Rec</b>	8.00
<b>TRA Code</b>	E2

## Load capacity (Kg)

	km/h / bar	9.00
	10	5600
	50	3530

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 14:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..