

EM 933 SUPER - Scheda tecnica



Description

EM 933 SUPER è stato appositamente progettato per gli scavatori in operazioni di scavo e di carico. L'eccezionale design del fianco con una nervatura sporgente del cordolo consente uno stretto contatto tra due pneumatici, eliminando la necessità di un anello di gomma speciale per impedire la penetrazione di pietre. L'esclusivo disegno del battistrada garantisce una trazione superiore in condizioni di servizio gravose. Altre caratteristiche dell'EM 933 SUPER sono l'eccezionale comfort di guida e le proprietà autopulenti.

UM

International Standard

Construction

 BIAS

Machinery

Industriale: Escavatore

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	OW	OD	Type
290/90 - 20	STANDARD	E2	152 B / 168 A2	18	8.00		295	1055	TT

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 11:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..