

EM 934 - Specifiche tecniche



Description

EM 934 è stato particolarmente sviluppato per escavatori nelle applicazioni per la costruzione delle strade, offrendo eccellente trazione laterale nonché straordinarie qualità di auto-pulitura. La miscela unica del battistrada è particolarmente resistente a tagli e lacerazioni mentre la carcassa robusta assicura una lunga vita operativa.

UM

US Standard

Construction

 BIAS

Machinery

Industriale: Escavatore

Version	SPECIAL
Type	TT
Tyre Size	10.00 - 20
LI/SS	146 B

Dimensions US Standard

Usa code	94054145
Ply Rating	16
Overall Width (inch)	11
Overall Diameter (inch)	41.7
Static Loaded Radius (inch)	19.7
Rolling Circumference (inch)	126.3
Rim Rec	7.5
Rim Alt	7.0 ; 8.0
TRA Code	E2

Load capacity (lbs)

mph / psi	109
30	6610

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24/11/2024 00:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..