

## EM 936 SUPER - Specifiche tecniche



### Description

EM 936 SUPER è stato specificamente progettato per escavatori e sollevatori telescopici nelle operazioni di scavo e carico nonché nelle applicazioni di trasporto. Grazie alla larghezza del battistrada incrementata dell'8-10%, EM 936 SUPER garantisce straordinaria stabilità e ottimo comfort di guida. Inoltre, lo pneumatico assicura un elevato comfort nelle manovre e fornisce eccellente trazione anche in condizioni di servizio pesante.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industriale: Escavatore

Version	STANDARD
Type	TT
Tyre Size	10.00 - 20
LI/SS	146 B

## Dimensions US Standard

Usa code	94062690
Ply Rating	16
Section Width (inch)	10.9
Overall Diameter (inch)	42.5
Static Loaded Radius (inch)	19.7
Rolling Circumference (inch)	131.3
Rim Rec	7.5
Rim Alt	7.0 ; 8.0
TRA Code	E2

## Load capacity (lbs)

mph / psi	108
30	6600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24/11/2024 03:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..