

EM 937 E3 (L) - Specifiche tecniche



Description

EM 937 (E-3/L-3) è stato particolarmente sviluppato per loader e terne nelle applicazioni di scavo e carico, a seconda della misura. Lo pneumatico si distingue per l'eccellente durabilità e l'ottima resistenza a tagli e strappi.

UM

US Standard

Construction

 BIAS

Machinery

Industriale: Terna • Pala caricatrice

Version	STANDARD
Type	TT
Tyre Size	14.00 - 25

Dimensions US Standard

Usa code	94015429
Ply Rating	24
Overall Width (inch)	14.8
Overall Diameter (inch)	53.9
Static Loaded Radius (inch)	24.4
Rolling Circumference (inch)	161.6
Rim Rec	10.00/1.5
TRA Code	E3/L3

Load capacity (lbs)

mph / psi	83	123
30	11400	-
5	-	20900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 02:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..