

FL 630 SUPER - Specifiche tecniche



Description

FL 630 SUPER è uno pneumatico Flotation idoneo per le applicazioni su campo e su strada con l'impiego di rimorchi, autobotti e spargitori. La sua struttura resistente offre un'eccellente trazione, durabilità e presa perfetta anche in curva e durante le manovre. Il particolare disegno del battistrada è sinonimo di elevata capacità di galleggiamento che riduce la compattazione del suolo oltre a proprietà di autopulitura avanzate. FL 630 SUPER può raggiungere velocità fino a 70 km/h.

UM

US Standard

Construction

 RADIAL

Machinery

Agricoltura: Spargitore • Autobotte • Rimorchio

Version	STANDARD
Type	TL
Tyre Size	650/65 R 26.5
LI/SS	174 D

Dimensions US Standard

Usa code	94045587
Section Width (inch)	25.4
Overall Diameter (inch)	59.8
Static Loaded Radius (inch)	26.9
Rolling Circumference (inch)	183.2
Rim Rec	AG 20.00
ECE	E4-106R-001651

Load capacity (lbs)

mph / psi	12	15	17	23	29	35	41	46	52	58
45	4310	4980	5650	6870	7940	9150	10360	11170	12380	13450
40	4730	5470	6210	7540	8720	10050	11380	12270	13590	14770
30	5730	6620	7520	9130	10550	12160	13770	14850	16460	17880
25	6440	7440	8440	10250	11860	13670	15480	16690	18500	20090
15	7470	8640	9810	11920	13780	15880	17980	19380	21480	23350
5	8510	9840	11180	13570	15700	18090	20480	22070	24470	26590

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/11/2024 20:45

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..